

KOHLER® POWER SYSTEMS



DESCRIPTIVE

- Kohler Co. Provides one-source responsibility for the generating system and accessories.
- The generator set and its components are prototype-tested, factory-built, and production-tested.
- A one-year limited warranty covers all systems and components
- (MTU/Mitsubishi/Volvo/John Deere) engine with 24-volt battery charging alternator.
- Leroy Somer single-bearing alternator with insulation class H.
- Radiator for core T° of 46°C max with mechanical fan.
- Skid and vibration isolators.
- Dry type air filter.
- Operation and installation literature.

POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1.

ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1.

Overload is not allowed

TERMS OF USE

According to the standard, the nominal power assigned by the genset is given for 25°C Air Inlet Temperature, of a barometric pressure of 100 kPA (100 m A.S.L), and 30 % relative humidity. For particular conditions in your installation, refer to the derating table.

ASSOCIATED UNCERTAINTY

For the generating sets used indoor, where the acoustic pressure levels depends on the installation conditions, it is not possible to specify the ambient noise level in the exploitation and maintenance instructions . You will also find in our exploitation and maintenance instructions a warning concerning the air noise dangers and the need to implement appropriated preventive measures.

KX1100

Engine type	16V2000G65F
Alternator type	LSA 49.1 L11

GENERAL CHARACTERISTICS

Frequency (Hz)	50
Reference voltage (V)	400/230
Max power ESP (kVA)	1100
Max power ESP (kWe)	880
Max power PRP (kVA)	1000
Max power PRP (kWe)	800
Intensity (A)	1588
Optional control panel	M80
Optional control panel	DEC4000
Optional control panel	KERYS

DIMENSIONS AND NOISE LEVELS

DIMENSIONS COMPACT VERSION

Length (in)	170
Width (in)	73
Height (in)	85
Dry weight (lbs)	14524

DIMENSIONS SOUNDPROOFED VERSION

Canopy	M427SSI
Length (in).	252
Width (in).	85
Height (in).	107
Dry weight (lbs).	21693
Tank capacity (gal).	246
Acoustic pressure level @1m in dB(A) (associated uncertainty)	87 (0.7)
Sound power level guaranteed (Lwa) in dB(A)	108

POWERS

Voltage	ESP		PRP		Standby Amps
	kWe	kVA	kWe	kVA	
415/240	880	1100	800	1000	1530
400/230	880	1100	800	1000	1588
380/220	880	1100	800	1000	1671

KX1100

ENGINE SPECIFICATIONS

GENERAL ENGINE DATAS

Engine model	MTU 16V2000G65F , 4-temps, Turbo , Air/Air DC 16 X
Cylinder arrangement	V
Displacement (C.I.)	1943.96
Bore (in) x Stroke (in)	5.12 x 5.91
Compression ratio	16
Speed (RPM)	1500
Pistons speed (ft/s)	24.61
Maximum stand-by power at rated RPM (BHP)	1306.97
Frequency regulation (%)	N/A
BMEP (psi)	324.17
Governor type	N/A

COOLING SYSTEM

Radiator & Engine capacity (gal)	N/A
Max water temperature (°F)	215.6
Outlet water temperature (°F)	203
Fan power (kW)	52
Fan air flow w/o restriction (cfm)	45619.49
Available restriction on air flow (in. WG)	0.79
Type of coolant	N/A
Thermostat (°C)	N/A

EMISSIONS

Emission PM (g/kW.h)	N/A
Emission CO (g/kW.h)	N/A
Emission HCNOx (g/kWh)	N/A
Emission HC (g/kW.h)	N/A

EXHAUST

Exhaust gas temperature (°F)	986
Exhaust gas flow (cfm)	6250.7
Max. exhaust back pressure (in WG)	19.69

FUEL

Consumption @ 110% load (gal/hr)	60.24
Consumption @ 100% load (gal/hr)	54.16
Consumption @ 75% load (gal/hr)	40.16
Consumption @ 50% load (gal/hr)	27.48
Maximum fuel pump flow (gal/hr)	158.52

OIL

Oil capacity (gal)	26.95
Min. oil pressure (psi)	68.17
Max. oil pressure (psi)	108.78
Oil consumption 100% load (gal/hr)	0.54
Carter oil capacity (gal)	24.31

HEAT BALANCE

Heat rejection to exhaust (Btu/mn)	N/A
Radiated heat to ambient (Btu/mn)	2561.38
Heat rejection to coolant (kW)	400

AIR INTAKE

Max. intake restriction (in. WG)	5.91
Intake air flow (cfm)	2330.77

GENERAL DATAS

Alternator brand	LEROY SOMER
Alternator type	LSA 49.1 L11
Number of phase	3
Power factor (Cos Phi)	0.8
Altitude (m)	0 à 1000
Overspeed (rpm)	2250
Number of pole	4
Excitation system	AREP
Insulation class / T° class, continuous 40°C	H / H / 125°K
Regulation	R450
Harmonic factor, no load TGH/THC	N/A
Wave form : NEMA=TIF-(TGH/THC)	N/A
Wave form : CEI=FHT-(TGH/THC)	N/A
Number of bearing	1
Coupling	Direct
Voltage regulation at established rating (%)	+/- 0.5%
Recovery time (Delta U = 20% transient) (ms)	500 ms

OTHER DATAS

Continuous Nominal Rating 40°C (kVA)	1000
Standby Rating 27°C (kVA)	1100
Efficiencies 4/4 load (%)	95
Air flow (cfm)	2542.66
Short circuit ratio (Kcc)	0.37
Direct axis synchro reactance unsaturated (Xd) (%)	346
Quadra axis synchro reactance unsaturated (Xq) (%)	207
Open circuit time constant (T'do) (ms)	2111
Direct axis transient reactance saturated (X'd) (%)	16.4
Short circuit transient time constant (T'd) (ms)	100
Direct axis subtransient reactance saturated (X''d) (%)	13.1
Subtransient time constant (T''d) (ms)	10
Quadra axis subtransient reactance saturated (X''q) (%)	14.3
Zero sequence reactance unsaturated (Xo) (%)	0.9
Negative sequence reactance saturated (X2) (%)	13.7
Armature time constant (Ta) (ms)	15
No load excitation current (io) (A)	0.8
Full load excitation current (ic) (A)	3.2
Full load excitation voltage (uc) (V)	38
Recovery time (Delta U = 20% transient) (ms)	500 ms
Engine start (Delta U = 20% perm. or 50% trans.) (kVA)	2372
Transient dip (4/4 load) - PF : 0,8 AR (%)	11.8
No load losses (W)	11050
Heat rejection (W)	41710

DIMENSIONS AND NOISE LEVELS

Canopy	M427
Length (in).	252
Width (in).	85
Height (in).	107
Dry weight (lbs).	21385
Tank capacity (gal).	246
Acoustic pressure level @1m in dB(A) (associated uncertainty)	91 (0.7)
Sound power level guaranteed (Lwa) in dB(A)	112

CIR20 SSI CONTAINER

Canopy	CIR20 SSi
Length (in).	239
Width (in).	96
Height (in).	114
Dry weight (lbs).	28682
Tank capacity (gal).	132
Acoustic pressure level @1m in dB(A)	80 (0.7)

DIMENSIONS AND NOISE LEVELS

ISO20 CONTAINER

Canopy	ISO20 Si
Length (in).	239
Width (in).	96
Height (in).	114
Dry weight (lbs).	25565
Tank capacity (gal).	132
Acoustic pressure level @1m in dB(A) (associated uncertainty)	88 (0.7)
Sound power level guaranteed (Lwa) in dB(A)	109

(associated uncertainty)
Sound power level guaranteed (Lwa) in
dB(A) 101

M80, transfer of information



The M80 is a dual-function control unit. It can be used as a basic terminal block for connecting a control box and as an instrument panel with a direct read facility, with displays giving a global view of your generating set's basic parameters.

Offers the following functions:

Engine parameters: tachometer, working hours counter, coolant temperature indicator, oil pressure indicator, emergency stop button, customer connection terminal block, CE

DEC4000, ergonomic and user-friendly



DEC4000

Specifications : Frequency meter, Ammeter, Voltmeter

Alarms and faults : Oil pressure, water temperature, No start-up, Overspeed, Min/max alternator, Min/max battery voltage, Low fuel level, Emergency stop

Engine parameters : Hours counter, Oil pressure, Water temperature, Engine speed, Battery voltage, Fuel level

KERYS, coupling and adaptability



The KERYS control unit has been designed to fulfil the specific requirements of professionals in terms of operating and monitoring generating sets. It therefore offers a wide range of functions.

This control unit is fitted as standard to all generating sets designed to be used for coupling and is offered as an option across the rest of our range.

The KERYS can be built into the central console, fitted directly on the generating set, or in a separate cabinet, to fulfil all the requirements for low and high output power plants.

The KERYS offers the following functions:

Electrical measurements: voltmeter, frequency meter, ammeter.

Engine parameters: working hours counter, oil pressure, coolant temperature, fuel level, engine speed, battery voltage.

Alarms and faults: oil pressure, coolant temperature, failure to start, overspeed, alternator min./max., battery voltage min./max., emergency stop.

Additional functions: coupling, website, diagnostic aid, assistance and maintenance, graphs and archiving, load impact management, 8 available installation configurations, certification in line with international standards.

For more information, please refer to the sales documentation.